





# Generating Satellite Climate Data Record over Canadian landmass

R. Latifovic, A. Trishchenko,
J. Chen, B. Park, R. Fernandes, D. Pouliot, K. Khlopenkov,
J. Cihlar, C. Ungureanu

2004 Satellite Direct Readout Conference Miami, Florida, December 6-10, 2004









Earth Sciences Sector

The objective of NRCan/ESS Program "Reducing Canada's Vulnerability to Climate Change" (RCVCC) is to contribute to the understanding of climate variability and change in order to enhance society's ability to plan and respond.











## Earth Science for National Action on Climate Change

## **Objective:**

Project is focused on the synthesis products used by national process (Joint Ministers) & Intergovernmental Panel on Climate Change

### **Project activities**

- 1) Radiation budget
- 2) Satellite records for CC
- 3) Ecosystem modeling
- 4) Water resources and vegetation dynamics
- 5) Cryosphere
- 6) Coastal zone









Long-term observations sustained over decades are a critical first-step in providing the climate data necessary for scientists, decision makers and stakeholders to make adaptive choices that could improve resilience to climate change and vulnerability, as well as maintain economic vitality.

### CDRs – Climate data records

Time series of measurements of sufficient length, consistency and continuity to determine climate variability and change. (NRC, 2004)

FCDRs – Fundamental climate data record.

Calibrated and quality-controlled sensor data that have been improved over time.

**TCDRs** – Thematic climate data record. Geophysical variable derived from the FCDRs such as surface temperature and cloud fraction.





#### Reducing Canada's vulnerability to climate change - ESS

## Why do we need CDRs?

#### ce for National Action on Climate Change



#### TIME SERIES 1980 - 2005

#### **Changes in vegetation phenology**

- Minimal, Maximal, Mean NDVI
- Amplitude in NDVI
- Total length of the growing season
- Fraction of growing season in green up
- Rate of green up
- Rate of senescence
- Integrated NDVI, green up, senescence, growing season

#### **Changes in surface characteristic**

- Winter summer albedo
- Minimal, maximal surface temperature
- Diurnal surface temperature cycle
- Snow cover
- Land cover and land cover change
- Leaf Area Index

#### **Changes in water characteristic**

- Lake surface temperature
- Diurnal lake surface temperature cycle
- Ice brake-up

#### **Radiation**

Statistics on cloud cover

#### **Trend**

NDVI LAI

Air\_Temperature

Radiation

Precipitation

Snow

Lake temperature

Forest fire

#### **Pattern**

Forest fire – NDVI-Air\_Temp-Radiation-Precipitation-Snow-Cloud

 $\label{eq:constraint} Drought-NDVI-Air\_Temp-Radiation-Precipitation-Snow-Cloud$ 

#Traffic Accidents- Air\_Temp-Precipitation-Snow-Cloud Household -Energy Consumption Sever weather events

#### **Models**





### Reducing Canada's vulnerability to climate change - ESS

J28 Earth Science for National Action on Climate Change

## **Satellite data**

Local Ar	ea Cove	rage (L	AC) and	High Re	esolutio	n Pictur	e Transı	mission	(HRP	T) Availa	bility B	ased on S	Satellite	Active	Archive
Satellite/ Year	TIROS-N	NOAA6	NOAA7	NOAA8	NOAA9	NOAA10	NOAA11	NOAA12	NOAA1	4 NOAA1	5 NOAA1	6 NOAA17	VGT 1	VGT2	MODIS
1979															
1980										Morning o	rbit				
1981										Afternoon orbit					
1982															
1983															
1984															
1985															
1986															
1987															
1988															
1989															
1990															
1991								,							
1992															
1993															
1994	- Ir	ı last 1	2 mor	the w											
1995															
1996		ollecte											<b>S10</b>		
1997		cenes													
1998		rchive		_											
1999	a	bout 9	.7TB c	of whic	h 📒										
2000	3	2848 (	3.3TB)	are			E.								
2001		IATAS			F-							- /			
2002					No.			THE REAL PROPERTY.					-12-1		
2003	-37.7												121		
2004		1 55	25 15	7 %		B-R 2	1 P. 13	15-							









## Satellite CDRs unique characteristic

- •Long term commitment to data collection and analysis.
- •The need for continual calibration, validation and algorithm refinement i.e. monitoring performance of multiple observing platforms for long-term applications.
- •Periodic reprocessing and reanalysis to improve error identification and reduce uncertainties.
- •The need for significant computational resources for processing, archiving and timely access to data and metadata.







## Source of inconsistency in long-term satellite records

- Different atmospheric condition during data acquisition.
- Imperfect image navigation i.e. georeferencing and resampling (variable pixel size).
- •BRDF effect due to variable viewing geometry.
- •Sensor and cross-sensor calibration (SRF, PSF).
- •Noise in internal calibration data (IR).
- •Variable illumination condition due to satellite orbit drift i.e. change in equatorial crossing time.





## Reducing Canada's vulnerability to climate change - ESS

J28 Earth Science for National Action on Climate Change



(AVHRR Processing System)

HRPT all formats, NATAS

Internal calibration data analysis and refinement

Georeferencing

Brower orbit model, TBUS archive 1983-2004, chip image data

Winter, summer day and night time orbit georeferencing and resampling

**Compositing** 

Include radiometric, acquisition geometry and georeferencing accuracy criteria

#### Post-seasonal data correction

(VGT Processing System)

Calibration and recalibration

Atmospheric correction using time dependent atmospheric conditions

**BRDF** normalization

Cloud screening

**Data analysis** 

Seasonal profile analysis


Time series














There are various unwanted fluctuations in thermal calibration data that can not be removed by standard quality control procedures and require robust techniques to be used











#### **Inter-Comparison of Large Scale Optical Sensors**







Reducing Canada's vulnerability to climate change - ESS

VIS and NIR calibration for National Action on Climate Change





















Georeferencing accuracy criteria

## Georeferencing

-Orbit model; TBUS (1983 – 2004) -GCP; chip matching










### TBUS data analysis








◆ NOAA 14 ■ NOAA 16



Compositing






Monthly composites of NOAA11 August of 1990











Corrected











S10 ES10










1995 Land cover




Multi-temporal land cover mapping 1990, 1995 and 2000 using data from NOAA11 and NOA14




2000 Land cover

#### 1990 Land cover






























#### LAI


SPOT-Vegetation 10-day 1km




**MODIS Monthly 1km** 




**POLDER 10-day (1/18 deg)** 



**MODIS LAIX20** 100



POLDER









Reducing Canada's vulnerability to climate change - ESS J28 Eart

LAI Validation over Canada Canadian VGT vs US MODIS ange





#### SPOT-Vegetation 10-day 1km





#### **MODIS Monthly 1km**













## Summary

- •Long-term observations sustained over decades are a critical first-step in providing the climate data necessary for scientists, decision makers and stakeholders to make adaptive choices that could improve resilience to climate change and vulnerability, as well as maintain economic vitality.
- •CDR's generated from long-term satellite observations have unique characteristics including periodical reprocessing and reanalysis. Thus, processing system need to be constantly improved as the new data correction methodology become available.
- •Significant initial steps in generating satellite CDR's over Canada have been accomplished under the ESS Program RCVCC and CSA GRIP project CCEI.
  - -AVHRR database that include 9.7 TB is established
  - -Core part of AVHRR and VGT processing system is developed
- •Today and near feature satellite sensors as ENVISAT–MERIS, NPOESS –VIIRS need to be assimilate in to CDRs.







## Reference:

Cihlar, J., R. Latifovic, J. M. Chen, A. Trishchenko, Y. Du, G. Fedosejevs, and B. Guindon, 2004. Systematic corrections of AVHRR image composites for temporal studies. Remote Sensing of Environment, 89, 217-233

Fernandes, R., Butson, C., Leblanc, S., & Larifovic, R. (2003), Landsat-5 TM and Landsat 7 ETM+ based accuracy assessment of leaf area index product for Canada derived from SPOT-4 VEGETATION data. Canadian Journal of Remote Sensing, 29, pp241-258

Latifovic, R., Cihlar, J., & Chen, J. M. (2003). A comparison of BRDF models for the normalisation of satellite optical data to a standard sun-target-sensor geometry. IEEE Transactions on Geoscience and Remote Sensing, 41, No.7

Latifovic, R. Zhu, Z., Cihlar J., Giri, C. and Olthof, I. (2004). Land cover mapping of North and Central America – Global Land Cover 2000. Remotes Sensing of Environment N.89. pp116-127

Teillet, P.M., & Holben, N.B. (1994). Towards operational radiometric calibration of NOAA AVHRR imagery in the visible and near infrared channels. Canadian Journal of Remote Sensing 20:1-10.

Trishchenko, A.P. (2002). Removing Unwanted Fluctuations in the AVHRR Thermal Calibration Data Using Robust Techniques. Journal Of Atmospheric and Oceanic Techniques Vol.19 No.12

Trishchenko, A.P., Cihlar, J. & Li, Z. (2001). Effects of spectral response function on surface reflectance and NDVI measured with moderate resolution satellite sensors. Remote Sensing Of Environment 81:1-18.



